Import Formats

- DICOM (version 3.0 and 2D stacks) including:
  - 4D (time-resolved) DICOM with time step selection
  - Option to store DICOM tags with imported data
- DICOMencapsulated STL surface models
- ACR-NEMA (versions 1 and 2)
- DICONDE
- Interfile
- Analyze
- Meta-image
- Raw image data
- 2D image stacks:
  - BMP
  - GIF
  - JPEG
  - PCX
  - PNG
  - TIFF
  - XPM
- Natively

  - ^ Statistics: default template for Mask, Model and Centerline statistics
  - ^ Number formatting: customize how numbers are formatted within Simpleware software
  - ^ Annotations: set default styles for annotations
  - ^ Scripting: enable/disable supported scripting languages
  - ^ Licensing: change license location
  - ^ Miscellaneous: reset suppressible dialogs, clear the undo/redo stack, mask name/color creation options
- x Interactive anatomy diagrams indicate the expected output, if anatomies are present and identifiable in the input data
- x Toggle segmentation of each available anatomy
- x Toggle the generation of landmarks
- x Landmarks accessible via the Measurements tool
- x Reduce region of interest to a sub-volume of a larger extent scan, either automatically or manually

2D User Interface

- x 3x 2D views
- x Orientation labels
- x Scale bars
- x DICOM information overlay
- x Interactive cropping using 2D view
- x Window/Level values and control options
- x Ability to work on single slice, selection of slices or whole volume
- x Slice cursors to identify the position of 2D slices
- x Mask visualization options: solid, translucent, voxel outline
- x View 3D model contours from model/3D view, surface objects and volume meshes on 2D slices
- x Multi-planar reconstruction through translation and rotation of reslicing axes

3D User Interface

- x Background volume rendering: using standard presets or greyscale mapping
- x Single mask volume rendering
- x Interactive cropping using 3D view
- x Clipping box: unconstrained, interactive sectioning of 3D rendering
- x Fast 3D preview mode for rapid visualization of segmentation: x

- Multi-label tools ^ use mask labels to label different regions within a mask. Use for statistics and visualization:
  - ^ Label disconnected regions
  - ^ Split mask into pores
  - ^ Combine masks to multi-label mask
  - ^ Mask label editor
  - ^ Reports (automatically generate pre-formatted reports of common metrics using a multi - Q F G J Q R F X P T W K Z Q Q R T I J Q c X mesh):
    - Particles report
    - Pores and throats report
- Window/level tool
- Overlap check: display/generate mask to check overlap volume in active masks

Ankle CT Segmentation and Landmarking

- Anatomy-specific automated segmentation tool for the ankle
- Automatic segmentation suitable for use on CT scans
- Produces masks for:
  - ^ Calcaneus
  - ^ Fibula
  - ^ Talus
  - ^ Tibia
- Landmarks placed on identified anatomy:
  - ^ Ankle center
  - ^ Fibular notch
  - ^ Malleolus (lateral, medial)
- Automatic ROI detection within larger extent scans
- Option to retain all bone fragments

Craniomaxillofacial (CMF) CT Segmentation and Landmarking

- Anatomy-specific automated segmentation tool for the CMF region
- Automatic segmentation suitable for use on CT scans
- Produces masks for:
  - ^ Cranium
  - ^ Cranium (filled orbitals)
  - ^ Mandible
  - ^ Ce [( )] TJ ET Q q 0.00000912 0 612 792 re W* n BT /F1 9 Tf 1 0 ET Q 9ET Q 9ET Q 9ET Q 9ET Q 9ET Q 9ET Q 9ET Q 9ET Q

- Resurface: use voxelization and iso-surface extraction to re-triangulate surface objects
- Clip: cut a surface object using finite plane
- Extrude: extrude selected triangles in a specified direction
- Hollow: hollow a surface object, creating an inner and outer surface
- Sweep: dilate the triangles of a surface object inwards and outwards to create a tube (Specialist option only)
- Auto-pad: auto pad the image boundary to contain surface object
- Feature edge editor: visualization and selection of feature edges that the meshing algorithms should try to preserve
- Interactive clipping box for section views of surface objects in 3D
- Surface deviation analysis tool ^ comparison of a test surface:
  - ^ Tool allows re-meshing of surfaces (user can set edge lengths required)
  - ^ Options to set distance limits for deviation analysis
  - ^ Surface deviation on regions of interest or the whole part can be calculated
  - ^ 3D color map with customizable scale, and option to set out of range color
  - ^ 3D color map also allows the user to set nominal and critical thresholds for positive and negative values
  - ^ Annotate visualization /Lang (en-US)>> BDC q Einamiu4(m)-16(s)8(a)11(n)5(d)4( )8(o)-16(a)11(px16(i)16(m)-16(iu4(m)-16(s)8 TJ ET Q q

- Multi-label mesh (and contact surfaces) export available for Abaqus (*.inp)

Multipart Volumetric Meshing

^ VTK files (*.vtk, *.vtu)

x